

## DAWN ENTERPRISES INC.

9155 Sweet Valley Dr., Valley View, OH 44125  
Phone: (216) 447-1777 or (800) 548-4867  
Fax: (216) 447-3416  
www.dawn-ent.com

## INSTALLATION INSTRUCTIONS

SS/ZINC

PART NUMBER: ACC08-4DR  
FOR: 2008 + Honda Accord 4 Door  
EFFECTIVE: 12.19.07

### INSTALLATION PACKAGE INCLUDES:

- A) 7 – Hole Locators (*center on each of six threaded sleeves of bottom of mounting feet, also one for the harness wire hole*)
- B) 4 – 5/8" Stainless Steel Machine Screws (*for outermost fastening are of the mounting feet*)
- C) 4 – Stainless Steel Lock Washers (*for outermost fastening area*)
- D) 2 – 5/8" Zinc Machine Screws (*for the innermost mounting area of mounting feet*)
- E) 2 – Zinc Lock Washers (*for innermost fastening area*)
- F) 2 – Electrical Connectors
- G) 1 – Wire Harness
- H) Instruction Sheet

### PLEASE READ ALL INSTRUCTIONS BEFORE BEGINNING INSTALLATION

**OPEN THE TRUNK AND PLACE A PROTECTIVE COVER INSIDE THE TRUNK TO CAPTURE ANY METAL SHAVINGS.**

1. Close trunk. **See Diagram on back of sheet.** Along the drivers' side measure down 7 ¾" from the tip of the trunk lid, back toward the rear of the car and make a mark with a grease pencil. Repeat on passenger side.
2. Place the Sportwing® on the marks made in Step #1. **See Diagram on back of sheet.** As you face the rear of the car, the front tips of the Sportwing® rests on these marks. Center the Sportwing® exactly from left to right. Using a grease pencil, outline both mounting feet. Remove Sportwing® from the trunk (**NOTE: by outlining mounting feet with grease pencil, you will be able to place the Sportwing® exactly back onto your desired position later in the installation when using paper hole locators**).
3. Turn Sportwing® upside down and place the paper hole locators centered over the threaded mounting hole sleeves on bottom of mounting feet (**NOTE: a small piece of masking tape is helpful in holding hole locators in place**). Place the Sportwing® back onto the outline marks that you made in Step #2. Making sure that the paper hole locators do not move. A second person is helpful when placing hole locators in place. When Sportwing® is in desired position, tape all seven hole locators in place onto deck lid. Next, carefully lift Sportwing® off of hole locators making sure locators stay in place on deck lid.
4. Using a 1/8" drill bit or similar size, drill a 1/8" hole through the exact center of the locators through the top panel of the deck lid only. After drilling all seven (7) holes on the deck lid and using a uni-bit (**NOTE: we suggest using a uni-bit for a cleaner cut**) you will need to open all seven 1/8" pilot holes to 3/8" only drilling through the top panel of the deck lid. Touch up edges of 3/8" holes using touch up paint.
5. Starting on the drivers' side, feed the brake light wires from the Sportwing® through the harness wire hole made in Step #4 (**NOTE: be careful not to crimp the brake light wires as you position the Sportwing® for installation**). Place the Sportwing® onto the outline marks made in Step #2 while holding the Sportwing® in place. Check to see that the 3/8" holes in the deck lid align with the threaded holes in the bottom of mounting feet. When satisfied with placement, using stainless steel screws with stainless steel lock washers, install screws half way when all six are started *tighten evenly*. **DO NOT OVER TIGHTEN.**
6. Feed the brake light wires of the Sportwing® through the ¼" WIRE HARNESS, provided. Using black electrical tape, fasten this harness neatly along side the factory harness, which runs down the drivers' side trunk hinge. Be sure to leave enough slack for opening and closing trunk lid. Run the wires toward the drivers' side taillight assembly and using top plug of taillight. Connect the Sportwing® (*red*) hot wire to the light green wire with silver slashes. Connect the (*black*) ground wire to the black wire with silver slashes. Test the connections by stepping on the brake pedal.
7. Clean up any metal shavings that might have fallen into the trunk and you are done. If you have any questions, problems or if you would like information about other quality Sportwing® products, please call the TOLL FREE number at the top of this sheet. Thank you for choosing Dawn Enterprises Inc.

